



Specifications for Hydro-Mix Tackifier

General

DRIWATER HYDRO MIX is an all-purpose tackifier consisting of non-toxic ingredients that quickly and easily mix with water, seed and mulch to produce a lump-free homogenous slurry. DriWater Hydro Mix binds all the components of the hydro-mulching system together which protects seeds from the damaging effects of the sun, allows for better water penetration into top soil and provides oxygen exchange without rapid moisture evaporation. DriWater is packaged in 9 lb. recyclable plastic bags and are sold six bags to a case.

Product

Furnish DRIWATER HYDRO MIX tackifier in a one or two step seeding process as specified by project engineer using hydro seeding equipment. Product may be applied also as a stand-alone tackifier at the same rates used in a seeding or mulching process.

Usage

When working on unstable or greater than 1:5-1 slopes use DriWater Hydro Mix in the first step of seeding process at 9lbs. per acre with seed and / or fertilizer.

Second step of the seeding / mulching process-Use Hydro Mix as tackifier with mulch using the following amounts:

2:1 to 1:1 (heavy rainfall or extreme wind sheers) slope -48lbs. / Acre

3:1 to 2:1 slope -27lbs. / Acre

Flat to 3:1 slope – 18lbs / Acre

Directions

Introduce the appropriate amount of DriWater Hydro Mix into a full mixing tank after all other components have been added, agitate mixture thoroughly. The amount of DriWater Hydro Mix to use will vary depending environmental and slope conditions.

Storage and Handling

To protect product quality, store original bags in a cool dry area. Surfaces subject to spill can become slippery.

Disclaimer: All information contained herein is offered in good faith. We warrant that the product conforms to the chemical description listed and is reasonably fit for the purposes set forth when used according to directions under normal use conditions. There are no other warranties whether expressed or implied, including warranty of fitness for a particular purpose. Our liability is limited to replacement of any product that does not meet these specifications

For further information or technical support please call (800) 255-8458
www.driwater.com